

PC 125/75 LG

Sample image

Order symbol : PC 125/75 LG

EAN : 6418074022080

Product nr : 6012309

El. number :

UL Name : UL PC 125/75 LG

- Finland : 3420325
- Denmark : 8212022072
- Sweden : 2535524

Description : Enclosure, PC

Remarks : Low base, grey cover

Including : Base with TPE gasket. screws for mounting plate/DIN-rail and cover with polyamide cover screws.

MNX125L

| Dimensions : | Height | Width | Depth |
|---------------------|---------------|--------------|--------------|
| mm : | 130 | 130 | 75 |
| inch : | 5.12 | 5.12 | 2.95 |

Materials :

| | |
|-------------------|----------------------|
| Material : | Polycarbonate |
| Base colour : | RAL_7035 |
| Cover colour : | RAL 7035 -light grey |
| Gasket material : | Polyurethane |

Temperatures :

| | |
|-------------------------------|-------------|
| Temperature °C (continuous) : | -40 ... 80 |
| Temperature °F (continuous) : | -40 ... 175 |

Accessories :

| | |
|----------|---|
| MIV 10 | DIN-35 Mounting rail, for enclosures: (100 x 35 x 7) |
| FP 22046 | Wall fastening lug (4 pcs) (35 x 16 x 10) |
| MIV 125 | Mounting plate (Galvanized steel), for enclosures: (98 x 98 x 1.5) |

Ratings :

| | |
|---|-------------------|
| Ingress protection (EN 60529): | IP66; IP67; |
| Impact Resistance (EN 62262): | IK08; |
| electrical_insulation : | Totally insulated |
| Halogen free (DIN/VDE 0472, Part 815) : | Yes |
| UV resistance : | UL 746C |
| Flammability Rating : | UL 94 V0 |
| Glow Wire Test (IEC 695-2-1) °C : | 960C |

Certificates :

Certificate FI 40847