

PC 300/150 ZG



Sample image

Order symbol : PC 300/150 ZG

Product nr : 6017338

Description : Enclosure, PC




Remarks : Grey cover

EAN : 6418074061515

El. number :

- Finland : 3435614
- Denmark : 8212027983
- Sweden : 2508686

Including : Base with TPE gasket. screws for mounting plate/DIN-rail and cover with polyamide cover screws.



Dimensions :	Height	Width	Depth
mm :	360	255	152
inch :	14.17	10.04	5.98

Materials :

Material :	Polycarbonate
Base colour :	RAL_7035
Cover colour :	RAL 7035 -light grey
Gasket material :	Polyurethane

Temperatures :

Temperature °C (continuous) :	-40 ... 80
Temperature °F (continuous) :	-40 ... 175

Accessories :

MIV 150	Mounting plate (Galvanized steel), for enclosures: (148 x 98 x 1.5)
MIV 200	Mounting plate (Galvanized steel), for enclosures: (223 x 148 x 1.5)
MIV 30	DIN-35 Mounting rail, for enclosures: (329 x 35 x 7)
MIV 15	DIN-35 Mounting rail, for enclosures: (150 x 35 x 7)
FP 10674	Wall fastening lug (2 pcs) incl. screws (40 x 88 x 14)
MIV 300	Mounting plate (Galvanized steel), for enclosures: (330 x 225 x 1.5)
MIV 20	DIN-35 Mounting rail, for enclosures: (225 x 35 x 7)

Ratings :

Ingress protection (EN 60529):	IP66; IP67;
Impact Resistance (EN 62262):	IK08;
electrical_insulation :	Totally insulated
Halogen free (DIN/VDE 0472, Part 815) :	Yes
UV resistance :	UL 746C
Flammability Rating :	UL 94 V0
Glow Wire Test (IEC 695-2-1) °C :	960C

Certificates :

Certificate FI 40847