

ARCA 403021W



Sample image

Order symbol : ARCA 403021W

Product nr : 8120127

Description : Cabinet. PC

Remarks : Grey cover. 2-point locking. hinges on the long side

EAN : 6418074079961

El. number :

- Finland : 3423200
- Denmark : 8212091838
- Sweden : 2500142

Including : Cabinet base. door with PUR gasket. mounting plate. screws for mounting plate. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.

| Dimensions : | Height | Width | Depth |
|---------------------|---------------|--------------|--------------|
| mm : | 400 | 300 | 210 |
| inch : | 15.75 | 11.81 | 8.27 |

Materials :

| | |
|-------------------|-------------------|
| Material : | Polycarbonate |
| Base colour : | RAL_7035 |
| Cover colour : | Clear transparent |
| Gasket material : | Polyurethane |

Temperatures :

| | |
|-------------------------------|-------------|
| Temperature °C (continuous) : | -40 ... 80 |
| Temperature °F (continuous) : | -40 ... 175 |

Accessories :

| | |
|-----------------|---|
| DRS ARCA 403021 | DIN rail frame set (385 x 285 x 35) |
| RCS ARCA 4030 | Rain canopy set for size 4030 and 3030 (30 x 300 x 20) |
| IDS ARCA 4030 | Inner door set (385 x 285 x 35) |
| PMK ARCA 30 | PoleMounting kit, for pole ø100-300mm (385 x 285 x 35) |
| DSP ARCA VLS | Door stopper ARCA, vertical, left, small (15 x 104 x 16) |
| MPMP ARCA 4030 | Mounting plate multiperforated (350x250x2 mm - ø3.6 mm) (350 x 250 x 1.5) |
| DSP ARCA VRS | Door stopper ARCA, vertical, right, small (15 x 104 x 16) |
| MPS ARCA 4030 | Mounting plate (350x250x2 mm) (350 x 250 x 2) |
| MPP ARCA 4030 | Mounting plate perforated (350x250x2 mm - 26x11 mm) (350 x 250 x 2) |
| MPX ARCA 4030 | Mounting plate (350x250 mm) (350 x 250 x 5) |

Ratings :

| | |
|--------------------------------|-------------------|
| Ingress protection (EN 60529): | IP65; |
| Impact Resistance (EN 62262): | IK08; |
| electrical_insulation : | Totally insulated |

| | |
|---|-----------|
| Halogen free (DIN/VDE 0472, Part 815) : | Yes |
| UV resistance : | UL 746C |
| Flammability Rating : | UL 94 5VA |
| Glow Wire Test (IEC 695-2-1) °C : | 960C |