

MANUFACTURERS DECLARATION

This declaration is to certify that the enclosure product line described below, conform to the following product characteristics.

Fibox CAB P

Technical information

<i>Material base</i>	<i>Glass Fibre Reinforced Polyester, RAL 7035</i>
<i>Material grey door</i>	<i>Glass Fibre Reinforced Polyester, RAL 7035</i>
<i>Material glazed door</i>	<i>Polycarbonate, clear transparent</i>
<i>Gasket</i>	<i>PUR</i>
<i>Ingress Protection (EN 60529)</i>	<i>IP65, IP66</i>
<i>Impact Resistance (EN 62262)</i>	<i>IK08 (grey door)</i>
	<i>IK07 (transparent door)</i>
<i>Max operating temp range long term</i>	<i>-40°C. . . +80°C</i>
<i>UV resistance</i>	<i>According to UL746C, the cabinets are suitable for outdoor use</i>
<i>Material Flammability Rating</i>	<i>UL 94-HB</i>
<i>Glow wire test</i>	<i>960°C</i>
<i>Static loads</i>	<i>Mounting plate 1 kg/dm²</i>
	<i>Mounting rail 10 kg/rail</i>
	<i>Cover/hinges 10kg</i>
	<i>Swing door/hinges 2kg</i>

Totally insulated
Halogen free compliance (DIN/VDE 0472, part 815)
Nominal voltage up to 1000 V AC and 1500 V DC

The products conforms to the standards:
EN 62208

The products fulfils the essential safety requirements for CE conformity marking according to the Low voltage Directive (2014/35/EU).



Allan Schultz Jensen
Director, Product Management