

MANUFACTURERS DECLARATION

This declaration is to certify that the enclosure product line described below, conform to the following product characteristics.

Fibox PICCOLO ABS

Technical information

<i>Base material</i>	<i>ABS</i>
<i>Cover material</i>	<i>ABS Grey, PC Transparent, gasket PUR</i>
<i>Base Colour</i>	<i>RAL 7035</i>
<i>Cover Colour</i>	<i>RAL 7035 or clear transparent</i>
<i>Ingress Protection (EN 60529)</i>	<i>IP66, IP67</i>
<i>Impact Resistance (EN 62262)</i>	<i>IK07 +35°C/-25°C</i>
<i>Max operating temp range long term</i>	<i>-40°C. . .+80°C</i>
<i>Material Flammability Rating</i>	<i>ABS UL 94-HB, PC UL 94-V0</i>
<i>Glow wire test</i>	<i>650°C</i>
<i>Static loads</i>	<i>Mounting plate 1 kg/dm²</i>

Totally insulated
Halogen free compliance (DIN/VDE 0472, part 815)
Nominal voltage up to 1000 V AC and 1500 V DC

The products conforms to the standards:
EN/IEC 62208

The products fulfils the essential safety requirements for CE conformity marking according to the Low voltage Directive (2014/35/EU).



Allan Schultz Jensen
Director, Products
Cabinets and Accessories