

MANUFACTURERS DECLARATION

This declaration is to certify that the enclosure product line described below, conform to the following product characteristics.

Fibox TEMPO ABS

Technical information

<i>Material</i>	<i>ABS, gasket PUR or TPE</i>
<i>Colour base</i>	<i>RAL 7035</i>
<i>Colour cover</i>	<i>RAL 7035 or clear transparent</i>
<i>Ingress Protection (EN 60529)</i>	<i>IP65</i>
<i>Impact Resistance (EN 62262)</i>	<i>IK07 +35°C/IK06 -25°C</i>
<i>Max operating temp range long term</i>	<i>-40°C. . . +80°C</i>
<i>Material Flammability Rating</i>	<i>UL 94HB, UL 94-V0 (transparent)</i>
<i>Glow wire test</i>	<i>650°C</i>
<i>Static loads</i>	<i>Mounting plate 1 kg/dm²</i> <i>Mounting rail 3 kg/rail,</i>
<i>Totally insulated</i>	
<i>Halogen free compliance (DIN/VDE 0472, part 815)</i>	
<i>Nominal voltage up to 1000 V AC and 1500 V DC</i>	

The products conforms to the standards:
EN 62208

The products fulfils the essential safety requirements for CE conformity marking according to the Low voltage Directive (2014/35/EU).



Allan Schultz Jensen
Director, Products
Cabinets and Accessories